



FILTERNOX KATAMARAN 412610 FILTER LAYOUT AND DIMENSIONS



Body Material:		AlSi 304
Screen Material:		AlSi 316
Max. Operating Pressure:		10 bar
Min. Inlet Pressure Required During back-flush:		2 bar
Max. Operating Temperature:		55 °C
Pressure Loss at Max. Flow Rate:		0.2 bar
Approximate back-flush Time:		4.0-6.0 sec. max.
Approximate back-flush Water Consumption:		300-400 l/back-flush
Coarse Screen back-flush Outlet:		Automatic valve
Fine Screen Control System:		Hydraulic or Electrical
Coarse Screen Control System:		Timer

For high pressure, high temperature and different materials, custom made filters can be produced.

INLET/OUTLET		FLANGE SIZES ND 10 - DIN 2576																		WEIGHT(kg)		MAX. FLOW RATE		SCREEN AREA
inch	mm	d	T	k	d ₁	n	t	A	L	L ₁	B	C	E	D	H	H ₁	P	P ₁	FULL	EMPTY	m ³ /h	cm ²		
10	250	273.1	395	350	22	12	26	900	2460	1700	312	910	338	12"	705	835	1275	2075	745	300	500	13000		

Inlet and Coarse Screen drainage directions can be used both ways for 8" (DN 200) and wider inlet-outlet diameter filters.
All dimensions are in millimeters.

Filternox reserves the rights to modify any of the technical information in this document without prior notification.