



# Bag Filter Vessel Series

## Specifications

- n Max operating pressure 8 bar g.
- n Max operating temperature = 50°C at operating pressure.  
For other conditions contact Parker Filtration.
- n Adjustable tripod legs galvanised carbon steel. Stainless steel tripod legs available at extra cost.

### Optional fittings for FH housings

- n Vent valve and "Bourdon" pressure gauge assembly.
- n Vent valve and "Schaeffer" pressure gauge assembly.
- n As an option, for the flanged version suitable threaded flanges are screwed on and welded before the final hydrostatic test for each housing.

## n Design Specifications

	Part Number	Bag Size	Dimensions mm					In/Outlet Size
			A	B	C	D	E	
Series 1	FHB1-50SG	Size 1 Bag	1025	350	204	173	150	ØG2
Series 2	FB11-2F	Size 2 Bag	1395	725	204	1731	150	ØG2

\* A trademark of E. I. du Pont de Nemours & Co.

\*\* Operating temperature limited to 250°F (121°C) by standard Buna-N O-ring and exterior paint on carbon steel models. Optional O-ring materials are available.

## Process Filtration Division

**Parker Filtration**  
Filter Division Europe  
Shaw Cross Business Park  
Dewsbury, West Yorkshire  
WF12 7RD, England  
Phone: +44 (0) 1924 487000  
Fax: +44 (0) 1924 487001  
Website: www.parker.com

